

TenPoint Core Features

TenPoint Series Core Performance Features

All TenPoint Series crossbows are made with a group of Core Performance Features (noted by black dot on callouts) that ensure accuracy, dependability, and durability regardless of the model you purchase. While our top-of-the-line models include additional premium features and benefits that make them undeniably the best in the industry, our Core Performance Features are the foundation upon which the entire series is built.

- Red dot indicates items that are exclusive to or were first introduced by TenPoint Crossbow Technologies.
- Black dot indicates a core performance feature.



Precision CNC machined aluminum wheels or cams (not on GT Curve)



The main assembly bolt's locking setscrew and the foot stirrup's two attachment setscrews are located on the underside of the crossbow's riser (foot stirrup setscrews not applicable to CLS models)



• • VIBRA-CUSH® patented bow-to-barrel mounting system

• Limb-bolt locking setscrews (only on the Lazer HP)



• • Optional ACUdraw (or ACUdraw 50) Patented Integrated Automated Cocking Unit (your choice included on CLS models) Available on all other models

3x Pro-View Scope (see scope lineup in accessories section)

• MIM (metal injection molded) CLAW-OVER string latch (on the PowerTouch triggers only)

Weaver-style machined aluminum 7/8" Dovetail Scope Mount

• • Synthetic cable yokes for the ultimate in tuneability and stability (not on GT Curve)

• IsoTaper Quad-Limb System (on CLS models only) (TenPoint's four quad-limb systems are model-specific to ensure optimum performance)

• • Optional Wedgie (patent pending) retention spring dampener (standard on CLS and Lazer HP models)

• CADD designed and engineered machined aluminum riser

• • ACUdraw-Ready FST Stock

ACRA-ARROW retention spring

• PBT Performance Cable Saver

• • OTT (over-the-top) limb-pocket and Zytel® "lift & separate" limb suspension system (not on GT Curve)

Sling swivel studs are standard equipment on all models

ACUdraw crank handle

• • Quiet MIM (metal injection molded) ambidextrous automatic safety

• • Patented DFI (dry-fire-inhibitor)

• Patented GripSafety secondary safety (only available on models with original Deluxe PowerTouch trigger)

Lightweight aluminum foot stirrup with sound-dampening rubber coating (CLS models have an extruded and machined one-piece foot stirrup and riser)

• Optional telescoping SteddyEddy Monopod System (included in Phantom Xtra and Phantom CLS packages)

• Patented PowerTouch trigger with MIM (metal injection molded) action components (the Titan TL-7 is equipped with our patent pending RollerTouch trigger)

• • ACRA-ANGLE Barrel

• • Power Limb-Tip Caps (GT Curve equipped with limb tips containing secondary field re-stringer shelf)

TenPoint's 4-Arrow Instant Detach HX Quiver

180-pound GT Recurve Limb system (only available on GT Curve)